





ARIES Surface Mounted Downlight

- Anti-glare
- Adjusting Shaft Design
- High-performance Chip



Aries Surface Mount Downlight - Single



Aries Surface Mount Downlight - Double

| Power | 15W | 20W | 30W | 40W |
|--------------------|-------------------------------|--------|-------------------------------|--------|
| Lumen Output | 975lm | 1300lm | 1950lm | 2600lm |
| Beam Angles | 15° 24° 30° 36° 60° | | 15° 24° 30° 36° 60° | |
| Colour Temperature | 2700K 3000K 4000K 5000K | | 2700K 3000K 4000K 5000K | |
| CRI | 92+ 97+ | | 92+ 97+ | |

Finishes

UV Textured White

IP 20

3yr Warranty

Dimmable

General Specifications

Material | Powder Coated Aluminium

Lifetime | >50,000h L70

Colour Deviation | SDCM≤3

Different dimming

Excellent thermal management

Driver

Power Factor | >0.90

240V Remote PC Dimmable Driver

Dimming Type | DALI, TRIAC, 1-10V

Notes

- Different wattage can be provided upon request
- Customization for non-standard solutions in terms of light source, color, length and other specifications.



ARIES Surface Mounted Downlight

Simple and delicate design, smooth and excellent painting, the surface mounted grille light performs well from inside to outlooking.