







Round

Square



Ø 90mm
(ϕ 80-85)

Ø 130mm
(ϕ 105-110)

Ø 90mm
(ϕ 80*80)

Ø 130mm
(ϕ 105*105)

| | | | | |
|--------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|
| Power | 8W 10W | 15W 20W 30W | 8W 10W | 15W 20W 30W |
| Lumen Output | 520lm 650lm | 975lm 1300lm 1950lm | 520lm 650lm | 975lm 1300lm 1950lm |
| Beam Angles | 15° 24° 30° 36° | 15° 24° 30° 36° 60° | 15° 24° 30° 36° | 15° 24° 30° 36° 60° |
| Colour Temperature | 2700K 3000K 4000K 5000K | 2700K 3000K 4000K 5000K | 2700K 3000K 4000K 5000K | 2700K 3000K 4000K 5000K |
| CRI | 92+ 97+ | 92+ 97+ | 92+ 97+ | 92+ 97+ |

Finishes

UV Textured White

IP 20

3yr Warranty

Dimmable

General Specifications

Material | Powder Coated Aluminium

Lifetime | >50,000h L70

Colour Deviation | SDCM \leq 3

Different dimming

Excellent thermal management

Driver

Power Factor | >0.90

240V Remote PC Dimmable Driver

Dimming Type | DALI, TRIAC, 1-10V

Notes

- Different wattage can be provided upon request
- Customization for non-standard solutions in terms of light source, color, length and other specifications.



MERCURY
Downlight

Round and Square shape design, meet your diversified demand and your indoor lighting design styles